Bollard RT3

B-6X10-FT-32D-SM-RT3

Satin Stainless Steel (630)





Features & Benefits

Competitive 4-week lead time

Ships from the factory to the job site in 20 business days or less.

Simple installation

Easy install of base mounting bracket and bollard body with stainless hardware and standard tools. Body can be detached from base without disturbing flooring for maintenance or replacement.

Secure mounting

1/2" diameter masonry anchors provided for mounting on pavers, concrete, or other flooring materials.

Welded flat top

Bollard cap is welded on and ground smooth for a watertight, seamless finish.

Preps for two devices

Includes cutouts for mounting intercoms, card readers, or actuators. Preps are customizable to fit make/model specified for each device.

Corrosion resistant body

Durable stainless steel construction for long-lasting use in both indoor and outdoor locations.

Specification Summary

Bollard overview:

- 1. Manufacturer: Wikk® Industries Inc.
- 2. Model: **B-6X10-FT-32D-SM-RT3**
- 3. Height: 48" (1219 mm)
- 4. Shape: 6" X 10" (152 mm x 254 mm)
- 5. Material: Satin Stainless Steel 304, .179" wall (4.5 mm)
- 6. Finish: Satin (US32D) #4 (630)
- 7. Top: Welded Flat
- 8. Mount: Concealed Surface Mount
- 9. Prep for Card Reader
- 10. Prep for Actuator
- 11. Country of Origin: Made in the U.S.A.

Optional Finishes:

- Long grain #6
- Mirror US32 (629)
- Non-directional

Countless custom options available!

Contact Wikk for custom short specs or budgetary and design assistance.

To ensure competitive bidding by qualified Sub Contractors, please specify Wikk's products in CSI Divisions: 8, 14, or 28.

