

Bollard RT5

B-6X12-FT-32D-SM-RT5

Satin Stainless Steel (630)

Phone: 877.421.9490
Fax: 877.421.3158
customerservice@wikk.com



Satin
Stainless
Steel Finish

INGRESS'R® Sold Separately

Specification Summary

Bollard overview:

1. Manufacturer: **Wikk® Industries Inc.**
2. Model: **B-6X12-FT-32D-SM-RT5**
3. Height: 42" (1067 mm)
4. Shape: 6" X 12" (152 mm x 305 mm)
5. Material: Satin Stainless Steel 304, .179" wall (4.5 mm)
6. Finish: Satin (US32D) #4 (630)
7. Top: Welded Flat
8. Mount: Concealed Surface Mount
9. Prep for I36 Series INGRESS'R®
10. Country of Origin: Made in the U.S.A.

Optional add-ons:

- Transmitter & receiver pair for wireless applications (available in 433 or 868 MHz)

Optional finishes:

- Long grain #6
- Mirror US32 (629)
- Non-directional

Countless custom options available!

Contact Wikk for custom short specs or budgetary and design assistance.

To ensure competitive bidding by qualified Sub Contractors, please specify Wikk's products in CSI Divisions: 8, 14, or 28.

Features & Benefits

Competitive 4-week lead time

Ships from the factory to the job site in 20 business days or less.

Simple installation

Easy install of base mounting bracket and bollard body with stainless hardware and standard tools. Body can be detached from base without disturbing flooring for maintenance or replacement.

Secure mounting

1/2" diameter masonry anchors provided for mounting on pavers, concrete, or other flooring materials.

Welded flat top

Bollard cap is welded on and ground smooth for a watertight, seamless finish.

Prep for INGRESS'R® mounting

Compatible with Wikk's 36" INGRESS'R® bar actuator for full range activation and ADA compliance.

Corrosion resistant body

Durable stainless steel construction for long-lasting use in both indoor and outdoor locations.

Wireless operation (Optional)

Transmitter & battery secured inside Ingress'R® housing for optimal transmission signal and convenient maintenance.

