

Bollard SQ10

B-6SQ-RT-32D-SM-INGR

Satin Stainless Steel (630)

Phone: 877.421.9490
 Fax: 877.421.3158
 customerservice@wikk.com



INGRESS'R® Sold Separately

Specification Summary

Bollard overview:

1. Manufacturer: **Wikk® Industries Inc.**
2. Model: **B-6SQ-RT-32D-SM-INGR**
3. Height: 42" (1067 mm)
4. Shape: 6" square (152 mm x 152 mm)
5. Material: Satin Stainless Steel 304, .120" wall (3.0 mm)
6. Finish: Satin (US32D) #4 (630)
7. Top: Removable Black Marine Board Cap
8. Mount: Concealed Surface Mount
9. Prep for I36 Series INGRESS'R®
10. Country of Origin: Made in the U.S.A.

Optional add-ons:

- Transmitter & receiver pair for wireless applications (available in 433 or 868 MHz)

Countless custom options available!

Contact Wikk for custom short specs or budgetary and design assistance.

To ensure competitive bidding by qualified Sub Contractors, please specify Wikk's products in CSI Divisions: 8, 14, or 28.

Features & Benefits

Competitive 4-week lead time

Ships from the factory to the job site in 20 business days or less.

Simple installation

Easy install of base mounting bracket and bollard body with stainless hardware and standard tools. Body can be detached from base without disturbing flooring for maintenance or replacement.

Secure mounting

1/2" diameter masonry anchors provided for mounting on pavers, concrete, or other flooring materials.

Weather-resistant cap secured with stainless steel set screws

Easy removal of leak-free mortised black marine board cap to access internal wiring. Cap material is resistant to fading or cracking in all environments.

Prep for INGRESS'R® mounting

Compatible with Wikk's 36" INGRESS'R® bar actuator for full range activation and ADA compliance.

Corrosion resistant body

Durable stainless steel construction for long-lasting use in both indoor and outdoor locations.

Wireless operation (Optional)

Transmitter & battery secured inside Ingress'R® housing for optimal transmission signal and convenient maintenance.

